

REPLACEMENT PARTS GUIDE

5039D Tractor (TREM IIIA Engine) (Worldwide Edition)



HYDRAULIC



FILTER ELEMENT [RE45864](#) (MITA)

[SJ11062](#) (USE WITH
JOHN DEERE ROCK-
SHAFT)

Replace after initial 100 hours and change every 500 hours and every 1250 hours.

ENGINE



OIL FILTER [RE507204](#) (For India) [T19044](#) (For Export)

Change every 100 hours and 250 hours.



PRIMARY AIR FILTER

[RE68048](#)

SECONDARY AIR FILTER

[RE68049](#)



Change after every 250 hours or annually which ever comes first. Change required.



PRIMARY FUEL FILTER

[RE508953](#)

FINAL FILTER

[RE508954](#)



Replace after every 500 hours.



JOHN DEERE

Genuine Parts and Service

CAPACITIES

5039D Tractor (TREM IIIA Engine) (Worldwide Edition)

CAPACITIES (Approximate):

Fuel Tank:

..... 60 L (13.19 gal)

**Crankcase including Filter Change:
Plus-50™**

..... 8.5 L (1.86 gal)

**Transmission and Hydraulic System:
Hy-Gard™**

Oil Axle 32 L (7.03 gal)


Grease Axle 30 L (6.56 gal)





REPLACEMENT PARTS GUIDE


5039D Tractor (TREM IIIA Engine) (Worldwide Edition)

ENGINE

 **BRAKE DISK**
[SJ18396](#) (2100 RPM)
(W/ HANDBRAKE)


 **ALTERNATOR**
[RE258846](#) (ALTERNATOR, 40 A)

 **CLUTCH DISK**
[SJ29350](#) (TRACTION)
[RE242274](#) (PTO)


 **FAN BELT DRIVE**
[SU63793](#) (LGTH = 1340 mm)



CAB

 **SEAT**
[SJ34660](#) (POWER STEERING)
[RE73192](#) (BOTTOM)
[RE212692](#) (BACK)

AXLE

 **TIE ROD**
[R225906](#) (W/ SCV)
[RE190506](#) (RH) (2WD)
[RE190481](#) (LH) (2WD)
[RE192255](#) (TIE ROD ASSEMBLY)
(2WD)