

REPLACEMENT PARTS GUIDE

9RT Tractors Final Tier 4 (FT4) - 9RT 470, 9RT 520, 9RT 570

ENGINE



DEF SUPPLY MODULE FILTER
[DZ114640](#) (FT4)

Replace after every 1500 operating hours or 3 years, whichever comes first.



DEF INLINE FILTER
[DZ124403](#) (FT4)

Replace after every 3000 operating hours or 3 years, whichever comes first.



PRIMARY AIR FILTER
[TA17973](#) (FILTER ELEMENT)

SECONDARY AIR FILTER
[RE230985](#) (FILTER ELEMENT)

Replace after every 1000 operating hours, annually, or as indicated, whichever occurs first. (Interval may vary according to operating conditions).



OIL FILTER
[RE572785](#)

Minimum hours before first engine oil change is 100 hours. Extended engine oil change every 500 hours or annually, whichever come first. The extended 500 hour interval is only allowed if using Plus50™ II oil with a John Deere filter and diesel fuel with sulfur content less than 15mg/kg (15ppm). If all conditions are not met, change oil and filter at 250 hours of operation.



PRIMARY FUEL FILTER
[DZ124761](#)
SECONDARY FUEL FILTER
[DZ124786](#)

Replace after every 500 operating hours or as indicated, whichever occur first.



FUEL WATER SEPARATOR FILTER
[AT365869](#) (If equipped)

Replace after every 500 operating hours.

TRANSMISSION



VENT FILTER
[H216169](#)



LUBE FILTER
[RE577612](#)



SYSTEM FILTER
[RE577250](#)

Replace after every 500 operating hours.



CAB



RECIRCULATION AIR FILTER
[RE593819](#)

Replace every 1000 hours or annually, whichever occurs first. (Interval may vary according to operating conditions).



FRESH AIR FILTER
[RE284091](#)

Replace every 1000 hours or annually, whichever occurs first. (Interval may vary according to operating conditions).

ENGINE



FUEL TANK VENT FILTER
[H216169](#) (QTY3)

Replace after every 1500 operating hours.

DRIVES



SUSPENSION COMPRESSOR FILTER
[RE556122](#)

Replace after every 1500 operating hours.

SVC



PILOT VALVE FILTER
[RE269061](#) (-926999)

[TA21586](#) (927001-)
Replace every 1500 operating hours.

REAR AXLE



OIL FILTER ELEMENT
[RE577612](#)

Replace every 1500 operating hours.

HYDRAULICS



HYDRAULIC OIL FILTER ELEMENT
[RE577612](#) (QTY 2)

Replace after every 1500 operating hours.



ENGINE DEF TANK VENT FILTER
[H216169](#) (FT4)

Replace after every 1500 operating hours.



STEERING PUMP FILTER
[RE577250](#)

Replace after every 1500 operating hours.



JOHN DEERE

Genuine Parts and Service

CLICK PART NUMBER TO BUY

*See operator's manual for additional details.

RX564271

Apr 2024. Release Date.

CAPACITIES

9RT Tractors Final Tier 4 (FT4) - 9RT 470, 9RT 520, 9RT 570

CAPACITIES (Approximate):

Fuel Tank

..... 1324 L (350 gal)

DEF Tank

..... 93.9 L (24.8 gal)

Cooling System (Including deaeration Tank):

Cool-Gard™ II

13.6 L Engine 56.5 L (14.9 gal)

CRANKCASE (including Filter):

Plus-50™ II

13.6 L Engine 60.8 L (16.1 gal)

HYDRAULIC / TRANSMISSION / REAR AXLE:

FULL COLD Mark 90.3 L (23.9 gal)

MIN COLD Mark 79 L (20.9 gal)

High Volume Take Out Oil Mark 126.3 L (33.4 gal)

Reservoir Volume Between

Min Cold and Full Cold Mark 11.4 L (3 gal)

HYDRAULIC / TRANSMISSION / AXLE OIL:











Without 3-Point Rear Hitch and PTO 330.8 L (87.4 gal)

With 3-Point Rear Hitch and PTO 338.4 L (89.4 gal)

REPIAR PARTS GUIDE






9RT Tractors Final Tier 4 (FT4) - 9RT 470, 9RT 520, 9RT 570

ENGINE





-  **STARTER**
[DZ121183](#)
-  **AUXILIARY DRIVE BELT**
[TR109574](#)
-  **FAN DRIVE BELT**
[R561692](#) - W/O AIR COMPRESSOR
[R563475](#) - W/ AIR TRAILER BRAKE
[R56408](#) -W/ CTIS COPRESSOR
-  **RADIATOR CAP**
[RE312969](#)
-  **BELT TENSIONER**
[AN208610](#) ENGINE
-  **ENGINE BLOCK HEATER**
[RE541654](#) - 120
[RE541655](#) - 240V
-  **WATER PUMP**
[DZ118003](#)
-  **A/C COMPRESSOR**
[RE326205](#)
-  **ALTERNATOR**
[DZ124336](#) - 330A
[DZ124395](#) - 250A
-  **FUEL INJECTION PUMP**
[DZ120832](#)





CAB

-  **INTERNAL REAR VIEW MIRRORS**
[RE588734](#)
-  **WIPER BLADES**
[R572234](#) FRONT, REAR & RHINDOW
-  **EXTERNAL REAR VIEW MIRROR**
[RE586098](#) LH
[RE586099](#) RH
-  **TECHNOLOGY MOUNTING SOLUTION**
[RE343680](#) ACCESSORY MOUNTING
[BRE10015](#) CELL PHONE MOUNTING
[BRE10255](#) TABLET MOUNTING BRACKET
-  **GAS CYLINDERS**
[TR126983](#) LH DOOR
[RE593531](#) REAR WINDOW

HITCH AND SCV

-  **HITCH MAINTENANCE**
[R309355](#) Sway Block, RH
[R304695](#) Sway Block Wear Plate, RH
[R309356](#) Sway Block, LH
[R304694](#) Sway Block Wear Plate, LH
-  **SCV**
[AXE14245](#) Hitch Position Sensor
-  **BREAKAWAY COUPLER**
[RE577560](#) BREAKAWAY COUPLER
[R186598](#) SNAP RING
[RE186600](#) SEAL KIT
-  **LIFT LINK PINS**
[RE333939](#) PIN
[R106409](#) DRAFT LINK BALL STUD

ENGINE

-  **BATTERY**
[TY25879B](#)
-  **TORSIONAL DAMPER**
[DZ117460](#)

