





REPLACEMENT PARTS GUIDE


330G Skid Steer Loader (PIN: 1T0330G__E314413-387237)





 **CAB FRESH AIR FILTER ELEMENT (IF EQUIPPED) - [AT441536](#)**
 **CAB RECIRCULATION AIR FILTER ELEMENT (IF EQUIPPED) - [AT359416](#)**
Interval (hrs) - As Required.

 **DUST UNLOADER VALVE [R48568](#)**
Interval (hrs) - As Required.


 **HYDRAULIC OIL FILTER [AT314164](#)**
Interval (hrs) - 1000.


 **HYDRAULIC OIL FILTER ELEMENT (IF EQUIPPED) [AT495722](#)**
Interval (hrs) - 1000.


 **FUEL TANK BREATHER [H216169](#)**
Interval (hrs) - 1000.


 **HYDRAULIC OIL RESERVOIR BREATHER [AT101565](#)**
Interval (hrs) - 500.





 **ENGINE AIR FILTER ELEMENT—PRIMARY**
PRIMARY - [KV16429](#)
SECONDARY - [AT171854](#)
Interval (hrs) - As Required.

 **ENGINE OIL FILTER [MIU800650](#)**
Interval (hrs) - 500.

 **ENGINE ROCKER ARM COVER GASKET [MIU802567](#)**
Interval (hrs) - 1500.

 **FINAL FUEL FILTER [MIU805005](#)**
Interval (hrs) - 500.

 **DIESEL PARTICULATE FILTER (DPF) (COMPONENT OF EXHAUST FILTER) [MIU804396](#)**
Interval (hrs) - As Required.

 **PRIMARY FUEL FILTER AND WATER SEPARATOR [MIU802421](#)**
Interval (hrs) - 500.



OILS AND CAPACITIES INFORMATION

330G Skid Steer Loader (PIN: 1T0330G___E314413-387237)

Part Description	Qty or capacity	Change Interval In Hours
John Deere Plus-50™ II Engine Oil ¹	12.6 L (3.3 gal)	500
John Deere Hydrau™ Hydraulic and Hydrostatic Oil ¹	33.1 L (8.7 gal)	1000
John Deere Hy-Gard™ Chain Case Oil per side) (330G and 332G only)	20.8 L (5.5 gal)	1000
John Deere Cool-Gard™ II Pre-Mix	14.9 L (3.9 gal)	6000
Fluid Analysis Test Kits ²		
Diesel Engine Oil	1	500
Hydraulic Oil	1	500
Engine Coolant	1	500
<p>¹See operator's manual for recommended oil type and oil viscosities based on operating temperatures.</p> <p>²Based on fluid analysis results, intervals may need to be adjusted for operating conditions. See an authorized John Deere dealer.</p>		

Plus-50 is a trademark of Deere & Company
Hydrau is a trademark of Deere & Company
Hy-Gard is a trademark of Deere & Company
Cool-Gard is a trademark of Deere & Company



Service Intervals

As Required	
<input type="checkbox"/> Check and clean cooling package	<input type="checkbox"/> Replace cab fresh air filter (if equipped)
<input type="checkbox"/> Check tire pressure	<input type="checkbox"/> Replace cab recirculation air filter (if equipped)
<input type="checkbox"/> Replace primary engine air filter element	<input type="checkbox"/> Check wheel lug nut torque
<input type="checkbox"/> Replace secondary engine air filter element (every 3rd primary element replacement or as required)	<input type="checkbox"/> Check accessory drive belt
<input type="checkbox"/> Check fuel tank breather	<input type="checkbox"/> Service exhaust filter
<input type="checkbox"/> Check and drain primary fuel filter and water separator	<input type="checkbox"/> Check and adjust steering mistracking
<input type="checkbox"/> Drain water and sediment from fuel tank	
Every 10 Hours or Daily	
<input type="checkbox"/> Check engine oil level	<input type="checkbox"/> Check hydraulic oil level
<input type="checkbox"/> Check coolant level	<input type="checkbox"/> Lubricate boom linkage, cylinder pivot points, and Quik-Tatch™ linkage
Every 50 Hours	
<input type="checkbox"/> Check and clean dust unloader valve	
Every 250 Hours	
<input type="checkbox"/> Take engine oil sample	
Every 500 Hours	
<input type="checkbox"/> Drain and refill engine oil and replace filter	<input type="checkbox"/> Check chain case oil level
<input type="checkbox"/> Replace primary fuel filter and water separator	<input type="checkbox"/> Take hydraulic oil sample
<input type="checkbox"/> Replace final fuel filter	<input type="checkbox"/> Take diesel fuel sample
<input type="checkbox"/> Replace hydraulic oil reservoir breather	<input type="checkbox"/> Take engine coolant sample
Every 1000 Hours	
<input type="checkbox"/> Check coolant condition	<input type="checkbox"/> Drain and refill hydraulic oil and replace hydraulic oil filter
<input type="checkbox"/> Replace fuel tank breather	<input type="checkbox"/> Drain and refill chain case oil
Every 1500 Hours	
<input type="checkbox"/> Check and adjust engine valve lash	
Every 6000 Hours	
<input type="checkbox"/> Drain and refill cooling system	