

# FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

## W110/W150 Windrowers

**CAB**  
RECIRCULATION AIR FILTER  
(W110) – [AFH209797](#)  
(W150) – [AFH208659](#)

Clean after every 100 hours and change as required.

**CAB**  
FRESH AIR FILTER (W110, W150)  
[AFH208656](#)

Clean after every 50 hours and replace as required.

**HYDRAULIC**  
HYDRAULIC FILTER (W110, W150)  
[AFH208689](#)  
[RE45864](#)

Replace after every 500 hours or each season, whichever comes first.

(Click here for [capacity](#))

**ENGINE**  
SECONDARY AIR FILTER (W110, W150)  
[PMAF25963](#)

Replace after every 250 hours or each season, whichever comes first.

**ENGINE**  
PRIMARY AIR FILTER (W110, W150)  
[PMAF25962](#)

Replace after every 250 hours or each season, whichever comes first.

**ENGINE**  
PRIMARY FUEL FILTER (W110, W150)  
[PMFS19732](#)

SECONDARY FUEL FILTER (W110, W150)  
[PMFF5612](#)

Replace after every 500 hours or each season, whichever comes first.

**ENGINE**  
OIL FILTER (W110, W150) – [PMLF3970](#)

Replace after every 250 hours or each season, whichever comes first.

(Click here for [capacity](#))



# CAPACITIES

## W110/W150 Windrowers

### CAPACITIES (Approximate):

#### Fuel Tank:

W110-W150 ..... 367 L (97 gal)

#### Cooling System:

##### Cool-Gard™ II

W110 ..... 25 L (6.6 gal)

W150 ..... 24 L (6.3 gal)

#### Engine Oil with Filter:

##### Plus-50™ II

W110-W150 ..... 11.9 L (3.14 gal)

#### Hydraulic System (Reservoir):

##### Windrower and Platform Lubricant 15W - 40

W110 ..... 44 L (11.62 gal)

W150 ..... 65 L (17.2 gal)

#### Final Drives Each:

GL-5 85W-140, Before Initial Change

GL-5 Fully Synthetic Gear Lubricant 75W-90, After Initial Change

W110-W150 ..... 1.4 L (0.36 gal)

#### Pump Drive Gear Case:

GL-5 Fully Synthetic Gear Lubricant 75W-90

W110-W150 ..... 2.1 L (0.55 gal)

[Return to Filter Overview](#)

