

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

3D Series Compact Utility Tractors - 3025D, 3035D, 3043D (North America Edition)

ENGINE

DIESEL PARTICULATE FILTER (DPF)

3035D – [MIU803093](#)

3043D – [MIU803276](#)

See your John Deere™ dealer or qualified service provider.



ENGINE

PRIMARY AIR FILTER – [SJ16911](#)

SECONDARY AIR FILTER – [SJ16914](#)

Check or replace after every 600 hours or as required.

ENGINE

FUEL/WATER SEPARATOR
[M811032](#)

Replace after every 400 hours or annually, whichever occurs first. See your John Deere™ dealer or qualified service provider.



ENGINE

PRIMARY FUEL FILTER – [MIU800645](#)

SECONDARY FUEL FILTER
(3035D AND 3043D) – [MIU803127](#)

Replace after every 400 hours or annually, whichever occurs first.



TRANSMISSION / HYDRAULIC
OIL FILTER – [RE45864](#)

Replace after every 400 hours and every 1200 hours or 3 years of operation, whichever is earlier.

(Click here for [capacity](#))



ENGINE

OIL FILTER – [M806419](#)

Replace after every 400 hours or annually, whichever occurs first.

(Click here for [capacity](#))



JOHN DEERE

Genuine Parts and Service

CAPACITIES

3D Series Compact Utility Tractors - 3025D, 3035D, 3043D (North America Edition)

CAPACITIES (Approximate):

Fuel Tank:

..... 38 L (10 gal)

Cooling System:

Cool-Gard™ II

3025D, 3035D 4.5 L (1.18 gal)

3043D 5 L (1.32 gal)

Crankcase with Filter:

Plus-50™

..... 4.3 L (1.1 gal)

Transmission / Hydraulic System:

..... 35 L (9.24 gal)

Front Axle:

Hy-Gard™

..... 3.8 L (1 gal)

[Return to Filter Overview](#)

