

# FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

## W155 Windrower



**CAB**  
**FRESH AIR INTAKE FILTER** [AFH208659](#)  
Clean after every 50 hours and change as required.

**CAB**  
**RETURN AIR FILTER** [AFH208656](#)  
Clean every 100 hours and replace as required.

**ENGINE**  
**FUEL STRAINER** [AFH212991](#)  
Replace each season.  
(Click here for [capacity](#))

**HYDRAULIC**  
**HYDRAULIC FILTER** [AFH208689](#)  
[RE45864](#)  
Replace after 500 hours or each season, whichever comes first.  
(Click here for [capacity](#))

**ENGINE**  
**DIESEL PARTICULATE FILTER** [RE565702](#)  
Replace after every 5500 hours and as required.

**ENGINE**  
**SECONDARY AIR FILTER** [PMAF55308](#)  
Replace each season and as required.

**ENGINE**  
**PRIMARY AIR FILTER** [PMAF55005](#)  
Replace after every 250 hours or each season, whichever comes first.

**ENGINE**  
**OPEN CRANKCASE VENTILATION (OCV) FILTER** [DZ105796](#)  
Replace every 1500 hours.

**ENGINE**  
**PRIMARY FUEL FILTER** [DZ115391](#)  
**SECONDARY FUEL FILTER** [DZ115390](#)  
Replace after every 500 hours or each season, whichever comes first.

**ENGINE**  
**OIL FILTER** [RE504836](#)  
Replace after every 250 hours or each season, whichever comes first.  
(Click here for [capacity](#))

**ENGINE**  
**DIESEL EXHAUST FLUID (DEF) DOSING UNIT FILTER** [DZ114640](#)  
Replace after every 4500 hours or every three years of operation, whichever comes first.  
(Click here for [capacity](#))



# CAPACITIES

## W155 Windrower

### CAPACITIES (Approximate):

#### **Fuel Tank:**

..... 367 L (97 gal)

#### **Cooling System:**

##### **Cool-Gard™ II**

..... 27.2 L (7.18 gal)

#### **Engine Oil with Filter:**

##### **Plus-50™ II**

..... 11.9 L (3.1 gal)

#### **Hydraulic System (Reservoir):**

##### **Windrower and Platform Drive Lubricant 15W - 40**

..... 65 L (17.2 gal)

#### **Diesel Exhaust Fluid (DEF) Tank:**

##### **John Deere™ Diesel Exhaust Fluid**

..... 14.1 L (3.75 gal)

#### **Final Drives Each:**

##### **GL-5 85W-140, Before Initial Change**

##### **GL-5 Fully Synthetic Gear Lubricant 75W-90, After Initial Change**

..... 1.4 L (0.36 gal)

#### **Pump Drive Gear Case:**

##### **GL-5 Fully Synthetic Gear Lubricant 75W-90**

..... 2.1 L (0.55 gal)

#### **Air-conditioning System:**

Air Conditioning Refrigerant ..... 2270 g (5 lb)

Air Conditioning Compressor Oil ..... 240 ml (8.1 fl. oz.)

[Return to Filter Overview](#)

