

SPECIFICATIONS

www.skidsteer.com

RAISING YOUR EXPECTATIONS WAS ALWAYS OURS.

240 Series II Skid Steer

- Patented vertical-lift system provides greater reach than conventional skid steers, for precise center load placement and quick, efficient truck loading.
- 53-hp John Deere 3029D high-torque engine with direct injection has exclusive wet-sleeve design, high-ring pistons, and precision joint-connecting rods. This easy-starting, durable engine is extremely fuel efficient.
- Quick-lift cab, removable side panels, and easy-access top and rear doors permit convenient maintenance and service.
- Superior 360-degree visibility results in greater productivity and safe operation. Unique boom arm design provides maximum bucket visibility.
- Available cab enclosure, air conditioner, and heater/defroster provide year-round climate control.
- Optional hydraulic Quik-Tatch™ latches/unlatches at the touch of a switch for convenient in-the-seat attachment switchover.
- Strong machine forces include — 5,500 lb. bucket breakout, 6,165-lb. operating weight, 4,450-ft.-lb. axle torque, and 3,400-lb. tipping load. Rated Operating Capacity (R.O.C.) is 1,500 lb. (2,000 lb. with optional counterweight).
- 114-in. hinge pin height easily clears 9-ft. truck sideboards for fast, efficient truck loading.
- Steep 45-degree dump angle and high 35-degree bucket rollback make for more efficient load carrying and quicker cycle times.

	240 Series II	Standard Equipment	Options/Accessories
Engine	John Deere	Adjustable Armrests, Patent Pending	Air Conditioning with Heater/Defroster
Model	3029D	Adjustable Foot Pedals	Auto Preheat
Displacement	179 cu. in. (2.9 L)	Air Heat Cold Start	Auto Shutdown with Alarm
Cylinders	3	Auxiliary Hydraulics	Backup Alarm
Horsepower	53 hp (39.5 kW) gross / 51 hp (38 kW) net	Convenient Front and Rear Tie Downs	Block Heater Kit
Rated Engine Speed	2,400 rpm	Deluxe Seat	Cab Enclosure
Fuel Capacity	15 U.S. gal. (57 L)	Four Grab Handles	Demolition Door Kit
Performance:		Front and Rear Work Lights	Dual Flashers Kit
SAE Rated Operating Capacity	1,500 lb. (681 kg)	Integral Cab Boom Locks	Floor Cover Plates
With Optional Counterweights	2,000 lb. (907 kg)	John Deere Manufactured Hydraulic Cylinders	Hand Controls
Tipping Load	3,400 lb. (1542 kg)	John Deere POWERTECH® Engine	Heater/Defroster Kit
Breakout Force:		Meters/Gauges/Warning Lights	High-Flow Hydraulics
Foundry Bucket	5,500 lb. (2495 kg)	Patented John Deere Quik-Tatch	Horn
Construction Bucket	3,900 lb. (1769 kg)	Patented Vertical-Lift Boom	Hydraulic Quik-Tatch
Ground Speed:		Quick-Pivot ROPS	Hydraulic Self-Leveling Kit
Single Speed	6.7 mph (10.8 km/h)	Rear Window	Quik-Tatch Weights
Maximum Axle Torque	4,450 ft.-lb. (6033 Nm)	Seat Belt with Auto Recoil	Rear Weight Brackets
Operating Weight	6,165 lb. (2796 kg)	Triple-Interlock Control System	Rearview Mirror Kit
Hydraulics:		Wet Disk Brakes	Shoulder Belt
Hydraulic Pressure	3,100 psi	8 pr. 10x16.5 SKS Extra-Wall Tires	Side Window Kit
Hydraulic Pump:		55-Amp Alternator	SMV Sign
Standard Flow	14.6 gpm (55.3 L/min.)		Suspension Seat
High Flow	25.4 gpm (96.1 L/min.)		Top Window
Hydraulic Horsepower:			Vinyl Cab Enclosure
Standard Flow	26.4 hp (19.7 kW)		Warning Beacon
High Flow	45.9 hp (34.2 kW)		3-Inch Seat Belt
Transmission	Hydrostatic four-wheel drive		8-Button Handle
Dimensions:			12-Volt Receptacle Kit
Length without Bucket	102 in. (2591 mm)		
Length with Bucket	125.8 in. (3196 mm)		
Width without Bucket	63.7 in. (1618 mm)		
Height to ROPS	75.4 in. (1915 mm)		
Height to Hinge Pin	114 in. (2895 mm)		
Dump Reach:			
Heavy-Duty Foundry Bucket	29.1 in. (738 mm)		
Heavy-Duty Construction Bucket	36.1 in. (917 mm)		
Dump Angle (At Full Height)	45 degrees		
Bucket Rollback (At Ground)	35 degrees		
Wheelbase	42.3 in. (1075 mm)		
Ground Clearance	8.2 in. (209 mm)		
Angle of Departure	27 degrees		
Standard Tire Size	10x16.5 SKS, Extra-Wall, 8-ply rating		
John Deere Standard Warranty	1-year unlimited hours		

John Deere Worksite Pro™ Attachments

- | | | |
|---|-----------------------|----------------------|
| Ag Utility Grapple | Hydraulic Breakers | Snow/Utility Blades |
| Angle Brooms | Multi-Purpose Buckets | Three-Point Hitch |
| Augers | Pallet Forks | Tined/Brush Grapples |
| Backhoes | Pick-Up Brooms | Tooth Bars |
| Bale Spear | Power Rakes | Tracks |
| Cold Planers | Rotary Tillers | Trenchers |
| Construction, Foundry, Manure/Slurry, and Utility Buckets | Scrap Grapples | Vibratory Rollers |

Due to various widths, not all attachment sizes offered are compatible with all 200 Series Skid Steers.

(Dimensions and specifications in accordance with SAE and ISO standards. Rated Operating Capacity with 66-in. Foundry Bucket and standard tires per SAE Standard J818.)



This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.



JOHN DEERE