

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

60 Series Four-Wheel Drive Tractors - 8560, 8760, 8960

ENGINE

OIL FILTER

- [DZ101880](#) (8560)
- [RE42051](#) and [RE21058](#) (8760; 8960 TSN -002527)
- [RE44647](#) (8960 TSN 002528-)

Initial oil and filter change at 100 hours and then after every 250 hours.
 Extend service interval by 50 hours when using John Deere Torq-Gard Supreme Plus-50 engine oil and a John Deere oil filter.
 (Click here for [capacity](#))




ENGINE

FUEL FILTER

- [AR86745](#) (8560, 8760)
- [RE42050](#) (8960)

FUEL WATER SEPARATOR (IF EQUIPPED)

- [RE11325](#) (8560, 8760)
- Replace after every 500 hours or as required.



CAB

RECIRCULATION AIR FILTERS


- [R112458](#) (8560 TSN 003101-; 8760 TSN 005101-; 8960 TSN 004101-)
- Replace annually or as required.



CAB

FRESH AIR FILTER

- [RE24619](#) (STANDARD)
 - [RE67829](#) (HEAVY-DUTY)
- Replace annually or as required.




ENGINE

SECONDARY AIR FILTER

- [AR70107](#) (8560)
- [AR95759](#) (8760, 8960)

Replace annually or as required.




ENGINE

PRIMARY AIR FILTER

- [AR70106](#) (8560)
- [AR95758](#) (8760, 8960)

Replace annually or as required.



ENGINE

COOLANT FILTER (IF EQUIPPED)

- [RE11992](#) (8760)
- Replace after every 500 hours.
 (Click here for [capacity](#))



TRANSMISSION/HYDRAULIC

OIL FILTER [RE38965](#)

CLEAN-UP OIL FILTER [AT112393](#)

Replace after every 250 hours, as required or as indicated - Power Shift
 Replace after every 750 hours, as required or as indicated - 12 speed & 24 speed.



SCREEN

- [RE35540](#) - POWER SHIFT
 - [R53169](#) - 12 SPEED & 24 SPEED
- Clean after every 1500 hours.
 (Click here for [capacity](#))



CAPACITIES

60 Series Four-Wheel Drive Tractors - 8560, 8760, 8960

CAPACITIES (Approximate):

Fuel Tank:

..... 835 L (220 gal)

Cooling System:

Cool-Gard™ II

8560, 8760..... 55 L (14.5 gal)

8960..... 68.1 L (18 gal)

Crankcase including Filter:

Plus-50™ II

8560..... 23 L (6.1 gal)

8760..... 34.5 L (9.1 gal)

8960..... 37 L (9.8 gal)

Hydraulic/Transmission System:

Hy-Gard™

Transmission 37.8 L (10 gal)

Hydraulic System 8560, 8760..... 144 L (38 gal)

Hydraulic System 8960..... 151 L (39.9 gal)

Hydraulic Reservoir 53 L (14 gal)

* All capacities are approximate. Please check Operator Manual for exact specifications.

[Return to Filter Overview](#)

