

# REPLACEMENT PARTS GUIDE

9R Tractors Final Tier 4 (FT4) - 9R 390, 9R 440, 9R 490, 9R 540, 9R 590, 9R 640

## FILTER OVERVIEW WITH SERVICE INTERVALS

### TRANSMISSION



#### VENT FILTER

[H216169](#)

Replace after every 1500 operating hours.



#### LUBE FILTER

[RE577612](#)

Replace after every 1500 operating hours.



#### SYSTEM FILTER

[RE577250](#)

Replace after every 1500 operating hours.

#### OIL FILTER

[RE572785](#) (13.6 L)

[DZ121669](#) (15 L)



Minimum hours before first engine oil change is 100 hours. Extended engine oil change every 500 hours or annually, whichever come first. The extended 500 hour interval is only allowed if using Plus50™ II oil with a John Deere filter and diesel fuel with sulfur content less than 15mg/kg (15ppm). If all conditions are not met, change oil and filter at 250 hours of operation.



#### PRIMARY FUEL FILTER

[DZ124761](#) FILTER ELEMENT (13.6 L)

[RE574467](#) FILTER ELEMENT (15 L)



#### SECONDARY FUEL FILTER

FILTER ELEMENT (13.6 L)

[DZ124786](#)

Replace after every 500 operating hours or as indicated, whichever occur first.



#### FUEL WATER SEPARATOR FILTER

[AT365869](#) (If equipped) (FILTER ELEMENT (13.6 L))

[RE561968](#) FILTER ELEMENT (15 L)

Replace after every 500 operating hours.



#### PRIMARY AIR FILTER

[TA17973](#) (FT4) (FILTER ELEMENT)

[HXE11090](#) (T2) FILTER ELEMENT



#### SECONDARY AIR FILTER

[RE230985](#) (FT4) (FILTER ELEMENT)

[HXE11091](#) (T2) FILTER ELEMENT

Replace after every 1000 operating hours, annually, or as indicated, whichever occurs first. (Interval may vary according to operating conditions).



### CAB



#### RECIRCULATION AIR FILTER

[RE593819](#)

Replace every 1000 hours or annually, whichever occurs first. (Interval may vary according to operating conditions).



#### FRESH AIR FILTER

[RE284091](#)

Replace every 1000 hours or annually, whichever occurs first. (Interval may vary according to operating conditions).

### SVC



#### PILOT VALVE FILTER

[RE269061](#)

Replace every 1500 operating hours.

### ENGINE



#### FUEL TANK VENT FILTER

[RE597019](#) (QTY 2)

Replace after every 1500 operating hours.



#### DEF INLINE FILTER

[DZ110513](#) (FT4)

Replace after every 3000 operating hours or 3 years, whichever comes first.



#### DEF SUPPLY MODULE FILTER

[DZ114640](#) (FT4)

Replace after every 1500 operating hours or 3 years, whichever comes first.



#### DEF TANK VENT FILTER

[H216169](#) (FT4)

Replace after every 1500 operating hours.

### HYDRAULICS



#### OIL FILTER ELEMENT

[RE577612](#) (QTY 3)

Replace after every 1500 operating hours.

For Company use: RX535024

Apr 2022. Release Date.



**JOHN DEERE**

Genuine Parts and Service

CLICK PART NUMBER TO BUY

\*See operator's manual for additional details.

# CAPACITIES

## 9R Tractors Final Tier 4 (FT4) - 9R 390, 9R 440, 9R 490, 9R 540, 9R 590, 9R 640

### CAPACITIES (Approximate):

#### Fuel Tank

..... 1514 L (400 gal)

#### DEF Tank

..... 120 L (31.7 gal)

#### Cooling System (Including deaeration Tank):

##### Cool-Gard™ II

13.6 L Engine ..... 56.5 L (14.9 gal)

15 L Engine ..... 62 L (16.3 gal)

#### ENGINE CRANKCASE OIL (including Filter):

##### Plus-50™ II

13.6 L Engine ..... 60.8 L (16.1 gal)

15 L Engine ..... 43.5 L (11.5 gal)

#### HYDRAULIC / TRANSMISSION / AXLE OIL:

Without 3-point rear hitch and PTO ..... 234.7 L (62 gal)

With 3-point rear hitch and PTO ..... 242.3 L (64 gal)

#### HYDRAULIC RESERVOIR REFERENCE MARKS:

FULL COLD Mark ..... 103 L (27.2 gal)

MIN COLD Mark ..... 91.8 L (24.3 gal)

High Volume Take Out Oil Mark  
(Dot half way up the sight tube) ..... 150 L (39.6 gal)

#### TRANSMISSION / HYDRAULIC RESERVOIR:

##### Hy-Gard™

Standard Flow ..... 208 L (55 gal)

High Flow ..... 212 L (56 gal)

# REPAIR PARTS GUIDE

9R Tractors Final Tier 4 (FT4) - 9R 390, 9R 440, 9R 490, 9R 540, 9R 590, 9R 640

## ENGINE



### STARTER

[DZ121183](#) - 13.6 L Engine

[RE589156](#) - 15 L Engine



### AUXILIARY DRIVE BELT

[TR109574](#) - 13.6 L Engine

[TR109575](#) - 15 L Engine



### FAN DRIVE BELT

[R561692](#) - W/O Air Compressor

[R563475](#) - W/ Air Trailer Brake

[R56408](#) - W/ CTIS Compressor



### RADIATOR CAP

[RE312969](#)



### BELT TENSIONER

[AN208610](#) - 13.6 L Engine

[REC410188400](#) - 15 L Engine



### ENGINE BLOCK HEATER

[RE541654](#) - 120 V, 13.6 L Engine

[RE541655](#) - 240 V, 13.6 L Engine

[REC496549700](#) - 15 L Engine



### WATER PUMP

[REC540604700](#) - 15 L Engine

[DZ118003](#) - 13.6 L Engine



### A/C COMPRESSOR

[RE326205V](#)



### ALTERNATOR

[DZ124336](#) - 330 A

[DZ124395](#) - 250 A



### Fuel Injection Pump

[DZ120832](#) - 13.6 L Engine

[REC435948900](#) - (-80266485),

15 L Engine

[REC549178400](#) - (80266486-),

15 L Engine



## CAB



### INTERNAL REAR VIEW MIRROR

[RE588734](#)



### WIPER BLADES

[R572234](#) - Front, Rear & RH Window




### EXTERNAL REAR VIEW MIRROR

[RE586098](#) - LH

[RE586099](#) - RH

[RE586100](#) - W/O Wide Angle



### TECHNOLOGY MOUNTING SOLUTION

[RE343680](#) - Accessory Mounting

[BRE10015](#) - Cell Point Mounting

[BRE10255](#) - Tablet Mounting Bracket



### GAS CYLINDERS

[TR126983](#) - LH Door

[RE593531](#) - Rear Window

## HITCH AND SCV



### HITCH MAINTENANCE

[R309355](#) - Sway Block, RH

[R304695](#) - Sway Block, Wear plate, RH

[R309356](#) - Sway Block, LH

[R304694](#) - Sway Block, Wear plate, LH

[AXE14245](#) - Hitch Position Sensor



### SCV

[RE577560](#) - Breakaway Coupler

[R186598](#) - Snap Ring

[RE186600](#) - Seal Kit



### LIFT LINK PINS

[RE333939](#) - Pin

[R106409](#) - Draft Link Ball Stud

## ENGINE



### BATTERY

[TY25879B](#)



### TORSIONAL DAMPER

[REC410188400](#) - 15 L Engine

[DZ117460](#) - 13.6 L Engine

For Company use: RX535024

Apr 2022. Release Date.



**JOHN DEERE**

Genuine Parts and Service

CLICK PART NUMBER TO BUY

\*See operator's manual for additional details.