

# FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

## W170 Windrower

**CAB**  
**FRESH AIR INTAKE FILTER** [AFH208659](#)  
 Clean after every 50 hours and change as required.



**ENGINE**  
**DIESEL PARTICULATE FILTER** [DZ104594](#)  
 Replace as required.  
 Note: When the exhaust filter and warning light indicators are alerted on the display, replace the DPF within 250 hours.

**ENGINE**  
**SECONDARY AIR FILTER** [PMAF25963](#)  
 Replace each season and as required.



**ENGINE**  
**PRIMARY AIR FILTER** [PMAF25962](#)  
 Replace after every 250 hours or each season, whichever comes first.



**ENGINE**  
**DIESEL EXHAUST FLUID (DEF) DOSING UNIT FILTER** [DZ114640](#)  
 Replace after every 4500 hours or every three years of operation, whichever comes first.  
 (Click here for [capacity](#))



**ENGINE**  
**OPEN CRANKCASE VENTILATION (OCV) FILTER** [DZ105100](#)  
 Replace every 1500 hours.



**CAB**  
**RETURN AIR FILTER** [AFH208656](#)  
 Clean every 100 hours and replace as required.



**HYDRAULIC**  
**HYDRAULIC FILTER** [AFH217822](#) **RETURN FILTER** [T175002](#) **CHARGE FILTER**  
 Replace after 500 hours or each season, whichever comes first.  
 (Click here for [capacity](#))



**ENGINE**  
**FUEL STRAINER** [FH318254](#)  
 Replace each season.  
 (Click here for [capacity](#))



**ENGINE**  
**PRIMARY FUEL FILTER** [DZ115391](#)  
**SECONDARY FUEL FILTER** [DZ115390](#)  
 Replace after every 500 hours or each season, whichever comes first.



**ENGINE**  
**OIL FILTER** [RE504836](#)  
 Replace after every 250 hours or each season, whichever comes first.  
 (Click here for [capacity](#))



# CAPACITIES

## W170 Windrower

### CAPACITIES (Approximate):

#### **Fuel Tank:**

..... 530 L (140 gal))

#### **Cooling System: Cool-Gard™ II**

..... 30 L (7.9 gal)

#### **Engine Oil with Filter: Plus-50™ II**

..... 11.9 L (3.1 gal)

#### **Hydraulic System (Reservoir): Hy-Gard™**

..... 58 L (15.3 gal)

#### **Diesel Exhaust Fluid (DEF) Tank: John Deere™ Diesel Exhaust Fluid**

..... 28 L (7.5 gal)

#### **Final Drives Each:**

**GL-5 85W-140, Before Initial Change**

**GL-5 Fully Synthetic Gear Lubricant 75W-90, After Initial  
Change**

..... 1.4 L (0.36 gal)

#### **Pump Drive Gear Case:**

**GL-5 Fully Synthetic Gear Lubricant 75W-90**

..... 2.1 L (0.55 gal)

#### **Air-conditioning System:**

Air Conditioning Refrigerant ..... 2270 g (5 lb)

Air Conditioning Compressor Oil ..... 240 ml (8.1 fl. oz.)

[Return to Filter Overview](#)

